



## AP - labels applicator

### Description

Primera's AP-Series Label Applicators are the perfect semi-automatic labeling solution for cylindrical containers as well as many tapered containers, including bottles, cans, jars and tubes.

### Apply labels fast and accurately

With AP-series label applicator you'll be able to apply labels at speed of up to 1200 per hour. Labels are perfectly applied without wrinkles, giving your finished products a highly professional look.

AP-series label applicators are an ideal accessory to Primera's LX or CX-series label printers. The applicators can also apply roll-fed, pressure-sensitive labels produced by most other flexographic, offset and digital presses.

### Features

- » Quick set-up and easy operation
- » Accurately applied labels to the front (AP360e) or front and back (AP362e) with variable spacing
- » Fast - labels are applied at 135 mm / s - up to 1200 containers / h
- » Compact size - fits on most desks and counter tops
- » Professionally designed - one of the only semi-automatic label applicators available with UL, CSA and FCC safety and emissions certificates
- » Industrial strength - built with heavy-duty sheet metal and steel for long life



**AG-FOIL BOHEMIA s.r.o.**

Bratislavská 3082, 690 02 Břeclav, CZ

Tel.: +420 519 323 815

Fax: +420 519 323 621

**Volejte ZDARMA: 800 233 332**

email: [office@agfoil.cz](mailto:office@agfoil.cz)

[www.agfoil.cz](http://www.agfoil.cz)

## Two models available

**AP360e** is the basic model. It quickly and efficiently applies single labels at a time.

**AP362e** is an advanced model. It can apply one or two different labels to a single container. A built-in LED counter and memory for up to nine front -to-back label offsets is also included.

## Set-up and operation is fast and easy.

- » 1. Set the guides
- » 2. Place your container in the machine
- » 3. Press the footswitch and your label is applied

The built-in spring-loaded pressure arm make sure labels are applied without wrinkles.

With an AP-series label applicator you'll apply labels faster and more accurately - helping to speed up your production and sell more of your products.

## Specifications

- » Container width: 25,4 mm - 238mm
- » Container diameter: 15 mm - 170 mm
- » Container Shape: cylindrical and more tapered
- » Supply roll diameter: up to 203 mm
- » Supply roll core: 51,4 mm - 76 mm
- » Media liner width: 25,4 mm - 213 mm
- » Electrical rating: 12 VDC, 5,0 A
- » Power requirements: 100 - 240 V, 50/60 Hz, 60 W
- » Agency certifications: UL, UL-C, CE, FCC Class A
- » Weight: 7,26 kg
- » Dimensions (WxHxD): 340 x 226 x 328 mm



**AG-FOIL BOHEMIA s.r.o.**

Bratislavská 3082, 690 02 Břeclav, CZ

Tel.: +420 519 323 815

Fax: +420 519 323 621

**Volejte ZDARMA: 800 233 332**

email: [office@agfoil.cz](mailto:office@agfoil.cz)

[www.agfoil.cz](http://www.agfoil.cz)